PHILIPS

MAS VLE
LEDBulbD3.4-40W E27
927 A60 CL G
929003070502



MASTER Value, LEDbulb, A60, dimmable, 40 W, E27, 2700 K, 470 lm, CRI 90, 15000 hour(s), Glass



MASTER Value, LEDbulb, A60, dimmable, 40 W, E27, 2700 K, 470 lm, CRI 90, 15000 hour(s), Glass, 138.00 lm/W, EEL D, PF 0.7, Beam angle 300 degree(s), RG0, IP65, SVM 0.4, PstLM 1

General Information

Cap-Base	E27
Nominal lifetime	15,000 hour(s)
Switching Cycle	20,000
Lighting Technology	LEDbulb
Flux measurement reference	Sphere
Warranty period	2.5 years

Light Technical

Color Code	927 [CCT of 2700K]
Beam Angle (Nom)	300 degree(s)
Luminous Flux	470 lm
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	138.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	90

LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RG0

Operating and Electrical

Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	3.4 W
Lamp Current (Nom)	20 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.7
Voltage (Nom)	220-240 V

Temperature

T-Case Maximum (Nom)	80 °C

Controls and Dimming

Dimmable	Only with specific dimmers

Mechanical and Housing

Bulb Finish	Clear
Bulb Material	Glass
Bulb Shape	A60
Net Weight (Piece)	0.030 kg

Approval and Application

Energy Efficiency Class	D
Energy Consumption kWh/1000 h	4 kWh
EPREL Registration Number	2607295
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +45 °C


Application Conditions

can it be used in closed luminaires	No
Wireless Technology	Not applicable

Product Data

Order product name	MAS VLE LEDBulbD3.4-40W E27 927 A60 CL G
Full product name	MAS VLE LEDBulbD3.4-40W E27 927 A60 CL G
Full product code	871951435481400
Order code	929003070502
Material Nr. (12NC)	929003070502
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514354814
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514354821


Dimensional drawing




D	C
60 mm	104 mm

Product	D	C
MAS VLE LEDBulbD3.4-40W E27 927 A60 CL G	60 mm	104 mm

Photometric data



Light Distribution Diagram - MAS VLE LEDBulbD3.4-40W E27 927 A60 CL G


General Uniform Lighting

1 x 9290030705 3.4W

1 x 470 lm

Polar intensity diagram

Quantity estimation diagram


UGR diagram

Utilisation factor table

Luminance Table


CalcuLuX Photometrics 4.5 Philips Lighting B.V. Page: 1/1

General uniform lighting - MAS VLE LEDBulbD3.4-40W E27 927 A60 CL G




Spectral Power Distribution Colour - MAS VLE LEDBulbD3.4-40W E27 927 A60 CL G

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - MAS VLE LEDBulbD3.4-40W E27 927 A60 CL G

Related Documents

Documents and certificates	Document Name	Download
Environmental Product Declaration	EPD-Philips-MASTER-Value-Glass-LED-bulbs-A60-COMF-8793345-Ref-929003057502-20240903-EPD.pdf	Download

Photometry and lighting design	Document Name	Download
IES File	LEDbulb_MAS_3,4W_A60_E27_927_CL-IES.IES	Download

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.