PHILIPS

CorePro LEDBulb7-60W E27 A60 840 FR G

929001323592



CorePro, LEDbulb, A60, not dimmable, 60 W, E27, 4000 K, 806 lm, CRI 80, 15000 hour(s), Glass



CorePro, LEDbulb, A60, not dimmable, 60 W, E27, 4000 K, 806 lm, CRI 80, 15000 hour(s), Glass, 115.00 lm/W, EEL E, PF 0.51, Beam angle 300 degree(s), RG1, IP20, SVM 0.4, PstLM 1

General Information

Cap-Base	E27
Nominal lifetime	15,000 hour(s)
Switching Cycle	20,000
Lighting Technology	LEDbulb
Flux measurement reference	Sphere
Warranty period	2 years

Light Technical

Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	300 degree(s)
Luminous Flux	806 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	115.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80

LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RG1

Operating and Electrical

Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	7 W
Lamp Current (Nom)	60 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.51
Voltage (Nom)	220-240 V

Temperature

T-Case Maximum (Nom)	50 °C

Controls and Dimming

Dimmable	No

Mechanical and Housing

Bulb Finish	Frosted
Bulb Material	Glass
Bulb Shape	A60
Net Weight (Piece)	0.030 kg

Approval and Application

Energy Efficiency Class	E
Energy Consumption kWh/1000 h	7 kWh
EPREL Registration Number	1825141
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +45 °C


Application Conditions

can it be used in closed luminaires	No
Wireless Technology	Not applicable

Product Data

Order product name	CorePro LEDBulb7-60W E27 A60 840 FR G
Full product name	CorePro LEDBulb7-60W E27 A60 840 FR G
Full product code	871951437751600
Order code	929001323592
Material Nr. (12NC)	929001323592
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514377516
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514377523


Dimensional drawing




D	C
60 mm	106 mm

Product	D	C
CorePro LEDBulb7-60W E27 A60 840 FR G	60 mm	106 mm

Photometric data



Light Distribution Diagram - CorePro LEDBulb7-60W E27 A60 840 FR G


General Uniform Lighting

1 x 9290013235

1 x 806 lm

Polar intensity diagram

Quantity estimation diagram


UGR diagram

Utilisation factor table

Luminance Table


CalcuLuX Photometrics 4.5 Philips Lighting B.V. Page: 1/1

General uniform lighting - CorePro LEDBulb7-60W E27 A60 840 FR G




Spectral Power Distribution Colour - CorePro LEDBulb7-60W E27 A60 840 FR G

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - CorePro LEDBulb7-60W E27 A60 840 FR G

Related Documents

Documents and certificates	Document Name	Download
Environmental Product Declaration	EPD-Philips-CorePro-Glass-LED-bulbs-COMF-8793379-Ref-929001387692-20240903-EPD.pdf	Download

Photometry and lighting design	Document Name	Download
IES File	LEDbulb_CLA_7W_A60_E27_840_FR-IES.IES	Download

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.