PHILIPS

**MAS ExpertColor**
**14.8-75W 930 AR111 24D**

929003042802




# MASTER, LEDspot, AR111, dimmable, 75 W, G53, 3000 K, 875 lm, CRI 95, 40000 hour(s)

MASTER, LEDspot, AR111, dimmable, 75 W, G53, 3000 K, 875 lm, CRI 95, 40000 hour(s), 59 lm/W, EEL G, PF 0.7, Beam angle 24 degree(s), RG1, IP20

## General Information

| | |
|---|---|
| Cap-Base | G53 |
| Nominal lifetime | 40,000 hour(s) |
| Switching Cycle | 50,000 |
| Lighting Technology | LEDspot |
| Flux measurement reference | Narrow Cone |
| Warranty period | 5 years |

## Light Technical

| | |
|---|---|
| Color Code | 930 [CCT of 3000K] |
| Beam Angle (Nom) | 24 degree(s) |
| Luminous Flux | 875 lm |
| Luminous Intensity (Nom) | 3,000 cd |
| Color Designation | White (WH) |
| Correlated Color Temperature (Nom) | 3000 K |
| Luminous Efficacy (rated) (Nom) | 59 lm/W |
| Color Consistency | <4 |
| Color rendering index (CRI) | 95 |
| LLMF At End Of Nominal Lifetime (Nom) | 70 % |
| Luminous Flux in 90° Cone (Rated) | 875 lm |
| Photobiological safety according to EN 62471 | RG1 |

## Operating and Electrical

| | |
|---|---|
| Line Frequency | 50 to 60 Hz |
| Input Frequency | 50 to 60 Hz |
| Power Consumption | 14.8 W |
| Lamp Current (Nom) | 1,500 mA |
| Wattage Equivalent | 75 W |
| Starting Time (Nom) | 0.5 s |
| Warm-up time to 60% light | 0.5 s |
| Power Factor (Fraction) | 0.7 |
| Voltage (Nom) | ac electronic 12 V |

## Temperature

| | |
|---|---|
| T-Case Maximum (Nom) | 85 °C |

## Controls and Dimming

| | |
|---|---|
| Dimmable | Only with specific dimmers |

## Mechanical and Housing

| | |
|---|---|
| Bulb Finish | Clear |
| Bulb Shape | AR111 |
| Net Weight (Piece) | 0.160 kg |

## Approval and Application

| | |
|---|---|
| Energy Efficiency Class | G |
| Suitable For Accent Lighting | Yes |
| Energy Consumption kWh/1000 h | 15 kWh |
| EPREL Registration Number | 648257 |
| CE mark | Yes |
| EU RoHS compliant | Yes |
| EyeComfort | Yes |
| Ambient temperature range | -20 to +45 °C |


## Application Conditions

| | |
|---|---|
| can it be used in closed luminaires | No |
| Wireless Technology | Not applicable |

## Product Data


| | |
|---|---|
| Order product name | MAS ExpertColor 14.8-75W 930 AR111 24D |
| Full product name | MAS ExpertColor 14.8-75W 930 AR111 24D |
| Full product code | 871951433383300 |
| Order code | 929003042802 |
| Material Nr. (12NC) | 929003042802 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8719514333833 |
| Numerator - Packs per outer box | 6 |
| EAN/UPC - Case | 8719514333840 |

## Dimensional drawing





| Product | D | C |
|---|---|---|
| MAS ExpertColor 14.8-75W 930 AR111 24D | 111 mm | 61 mm |

## Photometric data





Spectral Power Distribution Colour - MAS ExpertColor 14.8-75W 930 AR111 24D





Light Distribution Diagram - MAS ExpertColor 14.8-75W 930 AR111 24D

## Lifetime




Life Expectancy Diagram




Lumen Maintenance Diagram - MAS ExpertColor 14.8-75W 930 AR111 24D

## Related Documents

| Documents and certificates | Document Name | Download |
|---|---|---|
| Environmental Product Declaration | Philips-MASTER-LEDspot-LV-AR111-COMF-2165-Ref-929003042602-EPD.pdf | Download |

| Photometry and lighting design | Document Name | Download |
|---|---|---|
| IES File | LEDspots_MAS_SLR_14,8W_AR111_G53_930_24D-IES.IES | Download |

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.