PHILIPS

CorePro LED PLL HF 24W 830 4P 2G11

929001920402



CorePro, LED, PL-L, HF, 528 mm, 24 W, 55W PL-L, 3000 K, 3200 lm, CRI 83, 30000 hour(s)



CorePro, LED, PL-L, HF, 528 mm, 24 W, LED alternative to 55W PL-L, 3000 K, 3200 lm, CRI 83, 30000 hour(s), 133.00 lm/W, EEL E, 2G11, Beam angle 160 degree(s), Glass, RG0, SDCM 6, PF 0.9, IP20

General Information

Cap-Base	2G11
Nominal lifetime	30,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Warranty period	3 years

Light Technical

Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	160 degree(s)
Luminous Flux	3,200 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	133.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	83
LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RG0

Operating and Electrical

Line Frequency	20000-70000 Hz
Input Frequency	20000-70000 Hz
Power Consumption	24 W
Lamp Current (Max)	600 mA
Lamp Current (Min)	400 mA
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	53-77 V
LED alternative to fluorescent lamp power	55W PL-L
Inrush current at mains	-
Max. lamp no. on MCB B type 10A - Mains	-

Max. lamp no. on MCB B type 10A – EM ballast without Compensation Capacitor.	-
Max. lamp no. on MCB B type 10A – EM ballast with Compensation Capacitor.	-
Max. lamp no. on MCB B type 16A - Mains	-
Max. lamp no. on MCB B type 16A – EM ballast without Compensation Capacitor.	-
Max. lamp no. on MCB B type 16A – EM ballast with Compensation Capacitor.	-
Ballast Compatibility	HF

Temperature

T-Case Maximum (Nom)	70 °C


Controls and Dimming

Dimmable	No

Mechanical and Housing

Bulb Finish	Frosted
Bulb Material	Glass
Product Length	528 mm
Bulb Shape	PL-L
Net Weight (Piece)	0.160 kg

Dimensional drawing



D	D1	A1	A2	A3
38mm	17mm	453mm	528mm	535mm

Approval and Application

Energy Efficiency Class	E
Energy Saving Product	Yes
Approval Marks	RoHS compliance
Energy Consumption kWh/1000 h	24 kWh
EPREL Registration Number	387355
CE mark	Yes
EU RoHS compliant	Yes
Ambient temperature range	-20 °C to 45 °C

Application Conditions


Wireless Technology	Not applicable

Product Data


Order product name	CorePro LED PLL HF 24W 830 4P 2G11
Full product name	CorePro LED PLL HF 24W 830 4P 2G11
Full product code	871869682839700
Order code	929001920402
Material Nr. (12NC)	929001920402
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696828397
Numerator - Packs per outer box	10
EAN/UPC - Case	8718696828403

Product	D1	D	A1	A2	A3
CorePro LED PLL HF 24W 830 4P 2G11	17 mm	38 mm	453 mm	528 mm	535 mm


Photometric data



General uniform lighting - CorePro LED PLL HF 24W 830 4P 2G11




Light Distribution Diagram - CorePro LED PLL HF 24W 830 4P 2G11




Spectral Power Distribution Colour - CorePro LED PLL HF 24W 830 4P 2G11


Lifetime




LEDtube CorePro PLL HF 24W 2G11 830 24D ND




LEDtube CorePro PLL HF 24W 2G11 830 24D ND



Lumen Maintenance Diagram - CorePro LED PLL HF 24W 830 4P 2G11



LEDtube CorePro PLL HF 24W 2G11 830 24D ND



Lumen Maintenance Diagram - CorePro LED PLL HF 24W 830 4P 2G11

Related Documents

Documents and certificates	Document Name	Download
Installation Instructions	LEDtube_PLL_HF_Installation_Guide-INI.pdf	Download
Environmental Product Declaration	Philips-CorePro-LED-PLL-16-5W-840-4P-COMF-6714366-Ref-929001381602-EPD.pdf	Download

Photometry and lighting design	Document Name	Download
IES File	LEDtube_CorePro_PLL_HF_24W_2G11_830_24D_ND-IES.ies	Download

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.