PHILIPS

## CorePro LED PLL HF 24W 865 4P 2G11




929001920602

# CorePro, LED, PL-L, HF, 528 mm, 24 W, 55W PL-L, 6500 K, 3400 lm, CRI 83, 30000 hour(s)




CorePro, LED, PL-L, HF, 528 mm, 24 W, LED alternative to 55W PL-L, 6500 K, 3400 lm, CRI 83, 30000 hour(s), 141.00 lm/W, EEL E, 2G11, Beam angle 160 degree(s), Glass, RG0, SDCM 6, PF 0.9, IP20

### General Information

| | |
|---|---|
| Cap-Base | 2G11 |
| Nominal lifetime | 30,000 hour(s) |
| Switching Cycle | 50,000 |
| Lighting Technology | LED |
| Flux measurement reference | Sphere |
| Warranty period | 3 years |

### Light Technical

| | |
|---|---|
| Color Code | 865 [CCT of 6500K] |
| Beam Angle (Nom) | 160 degree(s) |
| Luminous Flux | 3,400 lm |
| Color Designation | Cool Daylight |
| Correlated Color Temperature (Nom) | 6500 K |
| Luminous Efficacy (rated) (Nom) | 141.00 lm/W |
| Color Consistency | <6 |
| Color rendering index (CRI) | 83 |
| LLMF At End Of Nominal Lifetime (Nom) | 70 % |
| Photobiological safety according to EN 62471 | RG0 |

### Operating and Electrical

| | |
|---|---|
| Line Frequency | 20000-70000 Hz |
| Input Frequency | 20000-70000 Hz |
| Power Consumption | 24 W |
| Lamp Current (Max) | 600 mA |
| Lamp Current (Min) | 400 mA |
| Starting Time (Nom) | 0.5 s |
| Warm-up time to 60% light | 0.5 s |
| Power Factor (Fraction) | 0.9 |
| Voltage (Nom) | 53-77 V |
| LED alternative to fluorescent lamp power | 55W PL-L |
| Inrush current at mains | - |
| Max. lamp no. on MCB B type 10A - Mains | - |

| | |
|---|---|
| Max. lamp no. on MCB B type 10A – EM ballast without Compensation Capacitor. | - |
| Max. lamp no. on MCB B type 10A – EM ballast with Compensation Capacitor. | - |
| Max. lamp no. on MCB B type 16A - Mains | - |
| Max. lamp no. on MCB B type 16A – EM ballast without Compensation Capacitor. | - |
| Max. lamp no. on MCB B type 16A – EM ballast with Compensation Capacitor. | - |
| Ballast Compatibility | HF |

## Temperature

| | |
|---|---|
| T-Case Maximum (Nom) | 70 °C |


## Controls and Dimming

| | |
|---|---|
| Dimmable | No |

## Mechanical and Housing

| | |
|---|---|
| Bulb Finish | Frosted |
| Bulb Material | Glass |
| Product Length | 528 mm |
| Bulb Shape | PL-L |
| Net Weight (Piece) | 0.160 kg |

## Dimensional drawing




| D | D1 | A1 | A2 | A3 |
|---|---|---|---|---|
| 38mm | 17mm | 453mm | 528mm | 535mm |

## Approval and Application

| | |
|---|---|
| Energy Efficiency Class | E |
| Energy Saving Product | Yes |
| Approval Marks | RoHS compliance |
| Energy Consumption kWh/1000 h | 24 kWh |
| EPREL Registration Number | 387357 |
| CE mark | Yes |
| EU RoHS compliant | Yes |
| Ambient temperature range | -20 °C to 45 °C |

## Application Conditions


| | |
|---|---|
| Wireless Technology | Not applicable |

## Product Data


| | |
|---|---|
| Order product name | CorePro LED PLL HF 24W 865 4P 2G11 |
| Full product name | CorePro LED PLL HF 24W 865 4P 2G11 |
| Full product code | 871869682843400 |
| Order code | 929001920602 |
| Material Nr. (12NC) | 929001920602 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8718696828434 |
| Numerator - Packs per outer box | 10 |
| EAN/UPC - Case | 8718696828441 |

| Product | D1 | D | A1 | A2 | A3 |
|---|---|---|---|---|---|
| CorePro LED PLL HF 24W 865 4P 2G11 | 17 mm | 38 mm | 453 mm | 528 mm | 535 mm |


## Photometric data




Light Distribution Diagram - CorePro LED PLL HF 24W 865 4P 2G11





General uniform lighting - CorePro LED PLL HF 24W 865 4P 2G11





Spectral Power Distribution Colour - CorePro LED PLL HF 24W 865 4P 2G11


## Lifetime





LEDtube CorePro PLL HF 24W 2G11 830 24D ND





LEDtube CorePro PLL HF 24W 2G11 830 24D ND




Lumen Maintenance Diagram - CorePro LED PLL HF 24W 865 4P 2G11




LEDtube CorePro PLL HF 24W 2G11 830 24D ND




Lumen Maintenance Diagram - CorePro LED PLL HF 24W 865 4P 2G11

## Related Documents

| Documents and certificates | Document Name | Download |
|---|---|---|
| Installation Instructions | LEDtube_PLL_HF_Installation_Guide-INI.pdf | Download |
| Environmental Product Declaration | Philips-CorePro-LED-PLL-16-5W-840-4P-COMF-6714366-Ref-929001381602-EPD.pdf | Download |

| Photometry and lighting design | Document Name | Download |
|---|---|---|
| IES File | LEDtube_CorePro_PLL_HF_24W_2G11_865_24D_ND-IES.ies | Download |

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.