PHILIPS

CorePro
LEDCandleND6.5-60W
B35 E14840CLG
929002028192



CorePro, LEDbulb, B35, not dimmable, 60 W, E14, 4000 K, 806 lm, CRI 80, 15000 hour(s), Glass



CorePro, LEDbulb, B35, not dimmable, 60 W, E14, 4000 K, 806 lm, CRI 80, 15000 hour(s), Glass, 124.00 lm/W, EEL E, PF 0.55, Beam angle 300 degree(s), RG1, IP20, SVM 0.4, PstLM 1

General Information

Cap-Base	E14
Nominal lifetime	15,000 hour(s)
Switching Cycle	20,000
Lighting Technology	LEDbulb
Flux measurement reference	Sphere
Warranty period	2 years

Light Technical

Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	300 degree(s)
Luminous Flux	806 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	124.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80

LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RG1

Operating and Electrical

Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	6.5 W
Lamp Current (Nom)	50 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.55
Voltage (Nom)	220-240 V

Temperature

T-Case Maximum (Nom)	55 °C

Controls and Dimming

Dimmable	No

Mechanical and Housing

Bulb Finish	Clear
Bulb Material	Glass
Bulb Shape	B35
Net Weight (Piece)	0.012 kg

Approval and Application

Energy Efficiency Class	E
Energy Consumption kWh/1000 h	7 kWh
EPREL Registration Number	1825172
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +45 °C


Application Conditions

can it be used in closed luminaires	No
Wireless Technology	Not applicable

Product Data

Order product name	CorePro LEDCandleND6.5-60W B35 E14840CLG
Full product name	CorePro LEDCandleND6.5-60W B35 E14840CLG
Full product code	871951434748900
Order code	929002028192
Material Nr. (12NC)	929002028192
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514347489
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514347496


Dimensional drawing



D	C
35 mm	97 mm

Product	D	C
CorePro LEDCandleND6.5-60W B35 E14840CLG	35 mm	97 mm

Photometric data


General Uniform Lighting

1 x 9290020281 B35 4000K 6.5W

1 x 806 lm

Polar intensity diagram

Quantity estimation diagram


UGR diagram

Utilisation factor table


Luminance Table

CalcuLuX Photometrics 4.5 Philips Lighting B.V. Page: 1/1

General uniform lighting - CorePro LEDCandleND6.5-60W B35 E14840CLG




Light Distribution Diagram - CorePro LEDCandleND6.5-60W B35 E14840CLG




Spectral Power Distribution Colour - CorePro LEDCandleND6.5-60W B35 E14840CLG

Lifetime



Lumen Maintenance Diagram - CorePro LEDCandleND6.5-60W B35 E14840CLG



Life Expectancy Diagram

Related Documents

Documents and certificates	Document Name	Download
Environmental Product Declaration	EPD-Philips-CorePro-Glass-LED-candles-and-luster-COMF-8799442-Ref-929001345392-20240903-EPD.pdf	Download

Photometry and lighting design	Document Name	Download
IES File	LEDcandle_E14_B35_840_CL-IES.ies	Download

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.