PHILIPS

MAS
LEDCandleDT5.9-60W
E14 927 B35 CL G
929003013982



MASTER, LEDbulb, B35, dimmable, 60 W, E14, 2200 K, 2700 K, 806 lm, CRI 90, 25000 hour(s), Glass



MASTER, LEDbulb, B35, dimmable, 60 W, E14, 2200 K, 2700 K, 806 lm, CRI 90, 25000 hour(s), Glass, 136 lm/W, EEL D, PF 0.6, RG0, IP65, SVM 0.4, PstLM 0.9

General Information

Cap-Base	E14
Nominal lifetime	25,000 hour(s)
Switching Cycle	20,000
Lighting Technology	LEDbulb
Flux measurement reference	Sphere
Warranty period	5 years

Light Technical

Color Code	922-927 [CCT of 2200K-2700K]
Luminous Flux	806 lm
Color Designation	Warm Glow(WG)
Correlated Color Temperature (Nom)	2200 K
Luminous Efficacy (rated) (Nom)	136 lm/W
Color Consistency	<6

Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RG0

Operating and Electrical

Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	5.9 W
Lamp Current (Nom)	40 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.6
Voltage (Nom)	220-240 V

Temperature

T-Case Maximum (Nom)	70 °C

Controls and Dimming

Dimmable	Only with specific dimmers

Mechanical and Housing

Bulb Finish	Clear
Bulb Material	Glass
Bulb Shape	B35
Net Weight (Piece)	0.013 kg

Approval and Application

Energy Efficiency Class	D
Energy Consumption kWh/1000 h	6 kWh
EPREL Registration Number	1109147
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	0.9
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 °C to 45 °C


Application Conditions

can it be used in closed luminaires	No
Wireless Technology	Not applicable

Product Data

Order product name	MAS LEDCandleDT5.9-60W E14 927 B35 CL G
Full product name	MAS LEDCandleDT5.9-60W E14 927 B35 CL G
Full product code	871951444957200
Order code	929003013982
Material Nr. (12NC)	929003013982
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514449572
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514449589


Dimensional drawing




D	C
35 mm	97 mm

Product	D	C
MAS LEDCandleDT5.9-60W E14 927 B35 CL G	35 mm	97 mm


Photometric data



Light Distribution Diagram - MAS LEDCandleDT5.9-60W E14 927 B35 CL G




General uniform lighting - MAS LEDCandleDT5.9-60W E14 927 B35 CL G




Spectral Power Distribution Colour - MAS LEDCandleDT5.9-60W E14 927 B35 CL G

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - MAS LEDCandleDT5.9-60W E14 927 B35 CL G

Related Documents

Documents and certificates	Document Name	Download
Environmental Product Declaration	EPD-Philips-MASTER-Glass-LED-candles-and-lusters-COMF-8793386-Ref-929003012282-20240903-EPD.pdf	Download

Photometry and lighting design	Document Name	Download
IES File	LEDbulb_MAS_EU3_5,9W_B35_E14_922_27_CL-IES.IES	Download

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.