
PHILIPS

CorePro
LEDLusterND2-25W P45
E27 827 CLG
929001238792



CorePro, LEDbulb, P45, not dimmable, 25 W, E27, 2700 K, 250 lm, CRI 80, 15000 hour(s), Glass



CorePro, LEDbulb, P45, not dimmable, 25 W, E27, 2700 K, 250 lm, CRI 80, 15000 hour(s), Glass, 125.00 lm/W, EEL E, PF 0.4, Beam angle 300 degree(s), RG1, IP20, SVM 0.4, PstLM 1

General Information

Cap-Base	E27
Nominal lifetime	15,000 hour(s)
Switching Cycle	20,000
Lighting Technology	LEDbulb
Flux measurement reference	Sphere
Warranty period	2 years

Light Technical

Color Code	827 [CCT of 2700K]
Beam Angle (Nom)	300 degree(s)
Luminous Flux	250 lm
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	125.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80

LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RG1

Operating and Electrical

Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	2 W
Lamp Current (Nom)	20 mA
Wattage Equivalent	25 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.4
Voltage (Nom)	220-240 V

Temperature

T-Case Maximum (Nom)	30 °C

Controls and Dimming

Dimmable	No

Mechanical and Housing

Bulb Finish	Clear
Bulb Material	Glass
Bulb Shape	P45
Net Weight (Piece)	0.014 kg

Approval and Application

Energy Efficiency Class	E
Energy Consumption kWh/1000 h	2 kWh
EPREL Registration Number	387364
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	-20 to +45 °C


Application Conditions

can it be used in closed luminaires	No
Wireless Technology	Not applicable

Product Data


Order product name	CorePro LEDLusterND2-25W P45 E27 827 CLG
Full product name	CorePro LEDLusterND2-25W P45 E27 827 CLG
Full product code	871951434776200
Order code	929001238792
Material Nr. (12NC)	929001238792
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514347762
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514347779

Dimensional drawing




Product	D	C
CorePro LEDLusterND2-25W P45 E27 827 CLG	45 mm	78 mm


Photometric data



Spectral Power Distribution Colour - CorePro LEDLusterND2-25W P45 E27 827 CLG




Light Distribution Diagram - CorePro LEDLusterND2-25W P45 E27 827 CLG




General uniform lighting - CorePro LEDLusterND2-25W P45 E27 827 CLG

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - CorePro LEDLusterND2-25W P45 E27 827 CLG

Related Documents

Documents and certificates	Document Name	Download
Environmental Product Declaration	EPD-Philips-CorePro-Glass-LED-candles-and-luster-COMF-8799442-Ref-929001345392-20240903-EPD.pdf	Download

Photometry and lighting design	Document Name	Download
IES File	LEDLuster_ND_2-25W_P45_827_CL_IES.ies	Download

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.